

**Field Mount - Multi-Channel - TDL Gas Analyzer**  
**ISA DATA SHEET**



<b>General</b>	1	Manufacturer	Boreal Laser Inc.	
	2	Analyzer Model No.	GasFinder3-MC (Multi-Channel) Assembly (e.g. BL-GF3-MC- - - - - - - - - -)	
	3	Measurement Head Model No.	N/A	
	4	Warranty Period	10 years on Laser (Light Source) and 3 years Full Warranty	
<b>Analyzer Performance</b>	5	Detection/Operating Principle	Tunable Diode Laser Absorption Spectroscopy (TDLAS)	
	6	Sensor Type / Number of Sensors	Semiconductor Diode Laser (NIR) / One (1) or Two (2) Lasers per GasFinder3-MC	
	7	Channels / Measurement Heads	One (1), Two (2), Three (3), or Four (4) Measurement Heads per GasFinder3-MC	
	8	Eye Safety	Class 1 AEL under IEC 60825-1	
	9	Function	Detects/monitors free gaseous molecules of one (1) or two (2) target gas(es)	
	10	Calibration	Factory calibrated with no requirement for periodic/inherent calibration	
	11	Field Calibration	None Required or Available	
	12	Automatic Validation	Internal Reference Cell (interrogated once a minute)	
	13	User Function Testing	External Response Cell to "bump", "test" or "challenge" (Optional Accessory)	
	14	Response Time	1.7 Seconds per Sample	
	15	Recovery Time	Instantaneous (Each sample is independent of the last)	
	16	Analyzer Mounting Location	Field (See Area Classification for more details)	
	17	Display / Local Indication	HMI Touchscreen (ppm-m, light level, alarm status, and fault status)	
	18	Accuracy	±2% of Reading	
	19	Internal Temperature Compensation	Dynamic (Piezo Resistive) or Manual Entry: -55°C to +150°C (-67°F to +302°F)	
	20	Internal Pressure Compensation	Dynamic (MEMS) or Manual Entry: 50 to 200 kPa Absolute (7.25 to 29 psia)	
	21	Drift	±0.1% over operating temperature and pressure ratings	
	22	Warm-up / Start-up Time	2 Minutes	
	23	User Intervention on Start-up	None Required	
	24	Operating Temperature	-55 to +65°C (-67 to 149°F)	
	25	Operating Humidity	0-100% RH (Non-Condensing)	
	26	Operating Pressure	50 to 200 kPa Absolute (7.25 to 29 psia)	
	27	Fault Diagnostics	Status Code visible via HMI Display, Interface, Outputs, and Logfiles	
	28	Internal Data Logging	User has access to 20 years worth of storage capacity via USB Stick	
	29	Safety Integrity Level	SIL2 Suitable	
	30	Obscuration / Beam Block	Operates down to 97% Obscuration (40x Turndown)	
	31	Solar Blind	No False Positives from Solar Interference	
	<b>Analyzer Enclosure</b>	32	Area Classification - Option #1	(A)Ex nA IIC T5 Tamb -45 to 65°C (Equivalent to: Class 1 Div/Zone 2 & Groups A,B,C,D)
		33	Area Classification - Option #2	(A)Ex nA IIC T6 Tamb -45 to 50°C (Equivalent to: Class 1 Div/Zone 2 & Groups A,B,C,D)
		34	Method of Protection	Non-Sparking/Non-Arcing "nA" (CSA No. 60079-15:16, ANSI/ISA 12.12.01-2015)
		35	Ingress Protection	IP 66 & NEMA Type 4X
36		RFI/EMI	N/A	
37		Enclosure Material	304 Stainless Steel	
38		Enclosure Mounting	Surface/Wall - 4 bolts in structure with 0.3125" nominal hole size	
39		Enclosure Dimensions (LxWxH)	495 x 368 x 160 mm (19.5 x 14.5 x 6.3 inches)	
40		Enclosure Weight	14 kg (31 lbs)	
41		Shipping Weight	16.6 kg (36.6 lbs)	
42		Storage Temperature	-55 to +65°C (-67 to 149°F)	
43		Power Cable Entry Size	One (1) 1/2" hole / M14 (left side of enclosure)	
44		Communication Cable Entry Size	Two (2) 3/4" holes / M20 (left side of enclosure)	
45		Measurement Head Cable Entry Size	Four (4) 3/4" holes / M20 (bottom of enclosure)	
46		Cable Glands: Power & Comm.	Supplied by others (as per local electrical standards)	
<b>Analyzer Power</b>		47	Power Consumption/Fuse	20 Watts under Normal Operation and 4A Fast Blow Cartridge Fuse (5x20 mm)
	48	In-Rush Current	Non-Hydrogen Fluoride (HF): 2.5A for 100ms & Hydrogen Fluoride (HF): 3.1A for 100ms	
	49	Input Voltage	24 VDC (Nominal) & 120-220 VAC (Available Option)	
	50	Power/Communication Terminals	2-Wire (16 awg)	
	51	Measurement Head Terminals	Single Mode Fiber Optic Cabling (FC/APC) and Shielded CAT6/5e Cabling (RJ-45)	
<b>Analyzer Interface Protocols</b>	52	Serial	USB (Data Download via USB Stick), & Micro USB (Realtime Data via GasView)	
	53	MODBUS	RS-485	
	54	HART	PV (ppm-m), SV (Light Level), TV (R2 Confidence Factor), & QV (TBD)	
<b>Analyzer Outputs</b>	55	Analyzer Board Stack Outputs	One (1) HART 7 enabled Non-Isolated/ Active Analog Loop and Digital Relay Output	
	56	Analog Module	Four (4) HART 7 enabled Isolated/ Active Analog Loops per Analog Module	
	57	Max. # of Analog Modules	GasFinder3-MC can support up to two (2) Analog Modules	
	58	Configurable Analog Output Options	ppm-m, ppm, mg/Nm3, Light Level (Rx), & R2 Confidence Factor	
	59	Analog Load Impedance	1,000 ohms (3 Devices)	
	60	Analog Range	2-20 mA	
	61	Low Light Alarm (Beam Block)	2.7 mA	
	62	General System Fault	3.6 mA	
	63	Relay Module	Six (6) Isolated Digital Relays per Relay Module (24 V, 1A Max)	
	64	Max # of Relay Module(s)	GasFinder3-MC can support up to four (4) Relay Modules	
	65	Configurable Relay Output Options	Hi-Alarm, Hi-Hi-Alarm, Low Light (Low Rx) Alarm, & General System Fault	
	66	Contact Relay Type	Voltage Free	
	67	Analog Range Settings	User Programmable via HMI Touchscreen or HART Communicator	
	68	Discrete Alarm Settings	User Programmable via HMI Touchscreen or HART Communicator	
	69	Analog/Discrete Low Light Time Delay	0 to 300 seconds - User Programmable via HMI Touchscreen or HART Communicator	

<b>Lo-Range Hydrogen Fluoride (HFL)</b>	70	Minimum Detectable Limit (MDL)	0.4 ppm-m
	71	Sensitivity	0.1 ppm-m
	72	Full Scale	250 ppm-m (analog range(s) are user programmable)
	73	Lowest Actionable Concentration	0.8 ppm-m (2x MDL)
	74	Maximum Recommended Path Length	500 m
	75	Maximum Recommended Cable Length	300 m
<b>Hi-Range Hydrogen Fluoride (HFH)</b>	76	Minimum Detectable Limit (MDL)	4 ppm-m
	77	Sensitivity	1 ppm-m
	78	Full Scale	1,000 ppm-m (analog range(s) are user programmable)
	79	Lowest Actionable Concentration	8 ppm-m (2x MDL)
	80	Maximum Recommended Path Length	500 m
	81	Maximum Recommended Cable Length	300 m
<b>Lo-Range Ammonia (NH3L)</b>	82	Minimum Detectable Limit (MDL)	8 ppm-m
	83	Sensitivity	2 ppm-m
	84	Full Scale	6,500 ppm-m (analog range(s) are user programmable)
	85	Lowest Actionable Concentration	16 ppm-m (2x MDL)
	86	Maximum Recommended Path Length	500 m
	87	Maximum Recommended Cable Length	300 m
<b>Hi-Range Ammonia (NH3H)</b>	88	Minimum Detectable Limit (MDL)	40 ppm-m
	89	Sensitivity	10 ppm-m
	90	Full Scale	15,000 ppm-m (analog range(s) are user programmable)
	91	Lowest Actionable Concentration	80 ppm-m (2x MDL)
	92	Maximum Recommended Path Length	500 m
	93	Maximum Recommended Cable Length	300 m
<b>Ultra Hi-Range Ammonia (NH3UH)</b>	94	Minimum Detectable Limit (MDL)	4,000 ppm-m
	95	Sensitivity	1,000 ppm-m
	96	Full Scale	1,000,000 ppm-m (analog range(s) are user programmable)
	97	Lowest Actionable Concentration	8,000 ppm-m (2x MDL)
	98	Maximum Recommended Path Length	500 m
	99	Maximum Recommended Cable Length	300 m
<b>Lo-Range Methane (CH4L)</b>	100	Minimum Detectable Limit (MDL)	2 ppm-m
	101	Sensitivity	0.5 ppm-m
	102	Full Scale	8,500 ppm-m (analog range(s) are user programmable)
	103	Lowest Actionable Concentration	4 ppm-m (2x MDL)
	104	Maximum Recommended Path Length	500 m
	105	Maximum Recommended Cable Length	300 m
<b>Hi-Range Methane (CH4H)</b>	106	Minimum Detectable Limit (MDL)	100 ppm-m
	107	Sensitivity	100 ppm-m
	108	Full Scale	500,000 ppm-m or 10 LEL-m (analog range(s) are user programmable)
	109	Lowest Actionable Concentration	200 ppm-m (2x MDL)
	110	Maximum Recommended Path Length	500 m
	111	Maximum Recommended Cable Length	300 m
<b>Lo-Range Hydrogen Sulphide (H2SL)</b>	112	Minimum Detectable Limit (MDL)	100 ppm-m
	113	Sensitivity	25 ppm-m
	114	Full Scale	100,000 ppm-m (analog range(s) are user programmable)
	115	Lowest Actionable Concentration	200 ppm-m (2x MDL) to 500 ppm-m
	116	Maximum Recommended Path Length	500 m
	117	Maximum Recommended Cable Length	300 m
<b>Hi-Range Hydrogen Sulphide (H2SH)</b>	118	Minimum Detectable Limit (MDL)	1,000 ppm-m
	119	Sensitivity	250 ppm-m
	120	Full Scale	500,000 ppm-m (analog range(s) are user programmable)
	121	Lowest Actionable Concentration	2,000 ppm-m (2x MDL)
	122	Maximum Recommended Path Length	500 m
	123	Maximum Recommended Cable Length	300 m
<b>Hydrogen Chloride (HCl)</b>	124	Minimum Detectable Limit (MDL)	2 ppm-m
	125	Sensitivity	0.5 ppm-m
	126	Full Scale	2,500 ppm-m (analog range(s) are user programmable)
	127	Lowest Actionable Concentration	1 ppm-m (2x MDL)
	128	Maximum Recommended Path Length	200 m (2-Channels Only)
	129	Maximum Recommended Cable Length	300 m (2-Channels Only)
<b>Hydrogen Cyanide (HCN)</b>	130	Minimum Detectable Limit (MDL)	8 ppm-m
	131	Sensitivity	2 ppm-m
	132	Full Scale	5,000 ppm-m (analog range(s) are user programmable)
	133	Lowest Actionable Concentration	16 ppm-m (2x MDL)
	134	Maximum Recommended Path Length	500 m
	135	Maximum Recommended Cable Length	300 m
<b>Lo-Range Carbon Monoxide (COL)</b>	136	Minimum Detectable Limit (MDL)	8 ppm-m
	137	Sensitivity	2 ppm-m
	138	Full Scale	8,500 ppm-m (analog range(s) are user programmable)
	139	Lowest Actionable Concentration	4 ppm-m (2x MDL)
	140	Maximum Recommended Path Length	50 m with one (1) OPX Head and 20m with two (2) OPX Heads
	141	Maximum Recommended Cable Length	5 m (2-Channels Only)
142	Special Note	Visible Laser function from Optical Multi-Meter will not work with COL Transceivers	

<b>Hi-Range Carbon Monoxide (COH)</b>	143	Minimum Detectable Limit (MDL)	250 ppm-m
	144	Sensitivity	60 ppm-m
	145	Full Scale	500,000 ppm-m (analog range(s) are user programmable)
	146	Lowest Actionable Concentration	500 ppm-m (2x MDL)
	147	Maximum Recommended Path Length	500 m
	148	Maximum Recommended Cable Length	300 m
<b>Ultra Lo-Range Carbon Dioxide (CO2UL)</b>	149	Minimum Detectable Limit (MDL)	0.4 ppm-m
	150	Sensitivity	0.1 ppm-m
	151	Full Scale	250 ppm-m (analog range(s) are user programmable)
	152	Lowest Actionable Concentration	0.8 ppm-m (2x MDL)
	153	Maximum Recommended Path Length	Saturation will occur over a 0.5m Path Length if measuring ambient concentrations
	154	Maximum Recommended Cable Length	20 m
<b>Lo-Range Carbon Dioxide (CO2L)</b>	155	Special Note	2-Channels Only & Atmospheric Concentrations can vary from 400-1,000 ppm
	156	Minimum Detectable Limit (MDL)	120 ppm-m
	157	Sensitivity	30 ppm-m
	158	Full Scale	60,000 ppm-m (analog range(s) are user programmable)
	159	Lowest Actionable Concentration	240 ppm-m (2x MDL)
	160	Maximum Recommended Path Length	100 m
<b>Hi-Range Carbon Dioxide (CO2H)</b>	161	Maximum Recommended Cable Length	20 m
	162	Special Note	2-Channels Only & Atmospheric Concentrations can vary from 400-1,000 ppm
	163	Minimum Detectable Limit (MDL)	500 ppm-m
	164	Sensitivity	150 ppm-m
	165	Full Scale	500,000 ppm-m (analog range(s) are user programmable)
	166	Lowest Actionable Concentration	2,000 ppm-m (2x MDL)
<b>Oxygen (O2)</b>	167	Maximum Recommended Path Length	500 m
	168	Maximum Recommended Cable Length	300 m
	169	Special Note	Atmospheric Concentrations can vary from 400-1,000 ppm
	170	Minimum Detectable Limit (MDL)	2,500 ppm-m
	171	Sensitivity	625 ppm-m
	172	Full Scale	1,000,000 ppm-m (analog range(s) are user programmable)
<b>Latest Revision</b>	173	Lowest Actionable Concentration	5,000 ppm-m (2x MDL)
	174	Maximum Recommended Path Length	4.5 m (Full Scale Saturation at Atmospheric Concentrations)
	175	Maximum Recommended Cable Length	300 m
	176	Special Note	The IR Laser Beam will be slightly visible and atmospheric concentration at 20.9%
	177		12/04/20